



**RL6000SA & RL6000SB Stretchtape™ Equivalent
 Silicone Rubber Self Fusing Electrical Insulating Tape
 500°F / 260°C: Meets MIL-I-22444, MIL-I-46852 / A-A-59163 & Many Other OEM
 Specifications**

Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing within minutes, fully bonded within hours. Excellent cold temperature performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening. Secures insulation to hot air ducting.
- Supported tape meets MIL-I-22444 and many other specifications.
- Certification available.
- Rolls are 12 yards long

RL6000SA & RL6000SB Stretchtape™ Equivalent Silicone Rubber Self Fusing Electrical Insulating Tape			
Part Number	Tape Width Inches / mm	Tape Thickness inches / mm	Price Per Roll
Supported Tape – With Fiberglass Substrate – 15% and 25% Maximum Elongation			
T-SR-RL6000SA-XX	1.00 / 25	0.020 / 0.51	\$ 67.29
T-SR-RL6000SB-XX	1.00 / 25	0.020 / 0.51	\$ 67.29

- For the XX value (color code): OR = Oxide-Red, BK = Black

T-SR-RL6000SA-XX equivalent to NSN 5970-01-325-8971

T-SR-RL6000SB-XX equivalent to NSN 5970-00-841-1172

Amalgamating time: At 120°C; 120 minutes / at 150°C; 35 minutes / at 200°C; 20 minutes / at 250°C; 15 minutes

Stretchtape™ is a trademark of Kirkhill-TA / Esterline